


Hydraulik-Schwenkspannzylinder SSZ 250



		Nutmutter DIN 1804				
		Kolben-ø	M	D	d	H
28	M16x1,5	32	27	7	5	
36	M20x1,5	36	30	8	6	
48	M26x1,5	45	40	10	7	
63	M38x1,5	58	50	11	8	

		Spannarm (auf Anfrage verschiedene Längen lieferbar)							
		Kolben-ø	D5f7	L _{sp}	B	H	L	L1	L11
28	16	50	30	25	75	15	4	17	M8
36	22	55	30	30	80	15	4	24	M10
48	30	60	45	45	95	22	4	30	M12
63	38	65	55	50	105	27	4	40	M16

		Vierkantflansch 112				
		Kolben-ø	D3	A	A1	D7
28	M45x1,5	90	62	11	14	
36	M52x1,5	100	70	13,5	16	
48	M65x1,5	110	80	13,5	20	
63	M85x2	130	102	17,5	25	

		Winkelflansch 113									
		Kolben-ø	D3	D9	B4	B5	B6	A7	A8	H1	H2
28	M45x1,5	13,5	80	110	12	30	50	40	70	14	
36	M52x1,5	17,5	90	130	15	35	65	50	90	16	
48	M65x1,5	17,5	110	140	20	45	80	65	110	20	
63	M85x2	21,5	130	170	25	50	90	80	135	25	

		Kontermutter DIN 1804				
		Kolben-ø	D3	D	d	H
28	M45x1,5	68	60	12	8	
36	M52x1,5	80	70	13	10	
48	M65x1,5	95	85	14	10	
63	M85x2	120	105	16	10	

Technische Änderungen vorbehalten

Revision C * 12.04.2013