


Hydraulic Block Cylinder HBZ 350

With aluminum housing and adjustable magnetic field sensors



	Attachment AD1 Axial attachment Through holes countersunk for cylinder head bolts on rod side. Ports: screw-in threads in inch		Attachment CD1 Axial attachment Through holes countersunk for cylinder head bolts on rod side. Ports: O-ring seals
	Attachment AD2 Axial attachment Through holes countersunk for cylinder head bolts on bottom side. Ports: screw-in threads in inch		Attachment CD2 Axial attachment Through holes countersunk for cylinder head bolts on bottom side. Ports: O-ring seals
	Attachment AG1 Axial attachment Threaded blind holes on rod side. Ports: screw-in threads in inch		Attachment CG1 Axial attachment Threaded blind holes on rod side. Ports: O-ring seals
	Attachment AG2 Axial attachment Threaded blind holes on bottom side. Ports: screw-in threads in inch		Attachment CG2 Axial attachment Threaded blind holes on bottom side. Ports: O-ring seals
	Attachment BD1 Radial attachment Through holes. Ports: screw-in threads in inch		Attachment DD1 Radial attachment Through holes. Ports: O-ring seals
	Attachment BG1 Radial attachment Threaded blind holes on left hand side. Ports: screw-in threads in inch		Attachment DG1 Radial attachment Threaded blind holes Anschlüsse: O-ring seals
	Attachment BG2 Radial attachment Threaded blind hole on right hand side. Ports: screw-in threads in inch		Attachment 120 Nondifferential cylinder Can be combined with all configurations. Ports: depending on Attachment

Piston-ø	16	20	25	32	40	50	63	80	100	125	160
Rod-ø	10	12	16	20	25	32	40	50	60	80	100
L	58	58	58	65	71	82	91	120	130	150	175
LD	72	66	67	78	85	103	108	138	142	167	190

Design subject to change

Revision B *18.03.13